



## GT General Range

GASTON GT range is the most common standard and the first generation delicate product which is designed with AGM(Absorbent Glass Mat) technology, high performance plates and electrolyte. The definition of GT is coming from General purpose. Therefore, this range product has possessed various applications for common power backup system.

### **Applications**

- Alarm System
- Cable Television
- Communication Equipment
- Control Equipment
- Security System
- Emergency Lighting System

- Medical Equipment
- UPS
- Power Tool
- Emergency Power System
- Toys & Powertool
- Stand-by Electric Power Control Equipment

## GT Range 2V,6V,8V,10V Monobloc Specifications

Model	Nominal Voltage (V)	Nominal Capacity (20hr)(Ah)	Dimensions						H Over Terminal		Weight Approx(kg)	
			L		W		H		(mm)	(in)	(Kg)	(lb)
			(mm)	(in)	(mm)	(in)	(mm)	(in)				
GT2-4.5	2	4.5	48	1.89	25	0.98	101	3.98	107	4.21	0.29	0.6
GT2-6	2	6	50	1.97	34	1.34	100	3.94	106	4.17	0.40	0.9
GT2-10	2	10	52.5	2.07	50	1.97	93	3.66	98	3.86	0.70	1.5
GT4-1	4	1.0	42	1.65	34.5	1.36	50	1.97	50	1.97	0.18	0.4
GT4-3.5	4	3.5	90	3.54	34	1.34	60	2.36	66	2.60	0.43	0.9
GT4-4.5	4	4.5	47.5	1.87	47.5	1.87	102	4.02	107	4.21	0.60	1.3
GT4-4.5A	4	4.5	52.5	2.07	48.5	1.91	93.5	3.68	99.5	3.92	0.60	1.3
GT4-5P	4	5	91	3.58	50	1.97	73	2.87	73	2.87	0.79	1.7
GT4-8P	4	8	91	3.58	50	1.97	102	4.02	102	4.02	1.13	2.5
GT4-9	4	9	102	4.02	44	1.73	95	3.74	101	3.98	1.10	2.4
GT4-10	4	10	102	4.02	50	1.97	94.5	3.72	100.5	3.96	1.33	2.9
GT6-1	6	1.0	51	2.01	42	1.65	51.5	2.03	57.5	2.26	0.27	0.6
GT6-1.3	6	1.3	97	3.82	24	0.94	52	2.05	58	2.28	0.30	0.7
GT6-1.7	6	1.7	70	2.76	47	1.85	101	3.98	107	4.21	0.33	0.7
GT6-2	6	2	75	2.95	51.1	2.01	53.2	2.09	59.2	2.33	0.35	0.8
GT6-2.3	6	2.3	42	1.65	37	1.46	76.5	3.01	76.5	3.01	0.37	0.8
GT6-2.5P	6	2.5	105	4.13	41	1.61	69	2.72	69	2.72	0.68	1.5
GT6-2.8	6	2.8	66	2.60	34	1.34	99	3.90	106	4.17	0.61	1.3
GT6-3.2	6	3.2	125	4.92	33	1.30	60	2.36	66	2.60	0.63	1.4
GT6-3.2H	6	3.2	67	2.64	34	1.34	115	4.53	121	4.76	0.66	1.5
GT6-3.4	6	3.4	134	5.28	35	1.38	61	2.40	67	2.64	0.67	1.5
GT6-4	6	4.0	70	2.76	47	1.85	101	3.98	107	4.21	0.71	1.6
GT6-4P	6	4.0	70	2.76	48	1.89	103	4.06	114.5	4.51	0.80	1.8
GT6-4.2	6	4.2	70	2.76	47	1.85	101	3.98	107	4.21	0.80	1.8
GT6-4.2S	6	4.2	70	2.76	47	1.85	104	4.09	105.5	4.15	0.80	1.8
GT6-4.2L	6	4.2	70	2.76	47	1.85	97	3.82	103	4.06	0.80	1.8
GT6-4.5	6	4.5	70	2.76	47	1.85	101	3.98	107	4.21	0.83	1.8
GT6-5L	6	5	67	2.64	67	2.64	96.5	3.80	113	4.45	1.00	2.2
GT6-5P	6	5	135	5.31	50	1.97	76	2.99	76	2.99	1.10	2.4
GT6-5.6	6	5	70	2.76	47	1.85	101	3.98	107	4.21	0.93	2.0
GT6-6	6	6	84.5	3.33	48	1.89	112	4.41	118	4.65	1.18	2.6
GT6-6A	6	6	94	3.70	47	1.85	102	4.02	108	4.25	1.05	2.3
GT6-7	6	7	151	5.94	34	1.34	94	3.70	100	3.94	1.20	2.6
GT6-7.5	6	7.5	151	5.94	34	1.34	94	3.70	100	3.94	1.23	2.7
GT6-7A	6	7	99	3.90	56.5	2.22	103	4.06	108	4.25	1.28	2.8
GT6-8P	6	8	135	5.31	50	1.97	101	3.98	101	3.98	1.69	3.7
GT6-8.5	6	8.5	98	3.86	55	2.17	118	4.65	118	4.65	1.90	4.2
GT6-10	6	10	151	5.94	50	1.97	94	3.70	100	3.94	1.85	4.1
GT6-12	6	12	151	5.94	50	1.97	94	3.70	100	3.94	2.05	4.5
GT6-12T	6	12	108	4.25	71	2.80	140	5.51	140	5.51	2.34	5.1
GT6-20	6	20	157	6.18	83	3.27	125	4.92	125	4.92	3.98	8.8
GT6-36	6	36	161	6.34	88	3.46	164	6.46	170	6.69	6.20	13.6
GT6-42	6	42	161	6.34	88	3.46	164	6.46	170	6.69	6.60	14.5
GT6-80	6	80	194.4	7.65	169.8	6.69	206.4	8.13	210	8.27	13.50	29.7
GT6-105	6	105	195	7.68	170	6.69	205	8.07	210	8.27	16.00	35.2
GT6-155	6	155	260	10.24	180	7.09	245	9.65	250	9.84	24.00	52.8
GT6-180	6	180	320	12.60	175	6.89	225	8.86	230	9.06	28.00	61.6
GT6-200	6	200	320	12.60	175	6.89	225	8.86	230	9.06	31.00	68.2
GT8-3.2	8	3	134	5.28	37	1.46	64	2.52	70	2.76	0.87	1.9
GT8-3.3	8	3.3	68	2.68	49	1.93	90.5	3.56	90.5	3.56	0.78	1.7
GT10-2	10	2	115	4.53	26	1.02	65.2	2.57	65.2	2.57	0.90	2.0