



GT-C Range

Gaston GT-C range (deep cycle) is designed specially to have a large amount of stored current discharged between charging sessions, with heavy non-porous battery plate that is made of a different chemical for the plates active paste material and a electrolyte stronger slightly than normal battery electrolyte. It enhances a superior performance of high power output and excellent deep cycle life for energy applications.

Applications

Electric Powered Vehicle
 Golf Cars and Buggy
 Wheel Chair
 Power Tool

Electric Powered Toy
 Control System
 Vacuum Cleaner
 Medical Equipment
 UPS

Specifications

Model	Nominal Voltage (V)	Nominal Capacity (20hr)(Ah)	Dimensions						H Over Terminal		Weight Approx(kg)	
			L		W		H		(mm)	(in)	(Kg)	(lb)
			(mm)	(in)	(mm)	(in)	(mm)	(in)				
GT6-4.5C	6	4.5	70	2.76	47	1.85	101	3.98	107	4.21	0.83	1.8
GT6-7C	6	8	151	5.94	34	1.34	94	3.70	100	3.94	1.36	3.0
GT6-12C	6	13.2	151	5.94	50	1.97	94	3.70	100	3.94	1.89	4.2
GT12-4.5C	12	4.5	90	3.54	70	2.76	101	3.98	107	4.21	1.70	3.7
GT12-7C	12	8	151	5.94	65	2.56	95	3.74	101	3.98	2.55	5.6
GT12-12C	12	13.2	151	5.94	98	3.86	95	3.74	101	3.98	4.00	8.8
GT12-14C	12	14	151	5.94	98	3.86	95	3.74	101	3.98	4.20	9.2
GT12-18C	12	20	181	7.13	77	3.03	167	6.57	167	6.57	6.00	13.2
GT12-26C	12	28	175	6.89	166	6.54	125	4.92	125	4.92	8.90	19.6
GT12-28C	12	28	165	6.50	126	4.96	175	6.89	182	7.17	8.50	18.7
GT12-30C	12	30	167	6.57	126	4.96	173	6.81	176	6.93	10.20	22.4
GT12-35C	12	35	195	7.68	130	5.12	159	6.26	180	7.09	10.50	23.1
GT12-40C	12	40	197	7.76	165	6.50	170	6.69	170	6.69	13.70	30.1
GT12-55C	12	56	229	9.02	138	5.43	206	8.11	226	8.90	17.00	37.4
GT12-65C	12	66	355	13.98	167	6.57	179	7.05	183	7.20	22.70	49.9
GT12-75C	12	76	258	10.16	168	6.61	208	8.19	226	8.90	23.00	50.6
GT12-90C	12	92	305	12.01	168	6.61	208	8.19	226	8.90	30.00	66.0
GT12-100C	12	102	330	12.99	172	6.77	215	8.46	221	8.70	31.00	68.2
GT12-100C-2	12	105	341	13.43	173	6.81	213	8.39	241	9.49	34.00	74.8
GT12-120C	12	122	405	15.94	175	6.89	208	8.19	235	9.25	38.00	83.6
GT12-134C	12	136	341	13.43	172	6.77	284	11.18	288	11.34	42.50	93.5
GT12-150C	12	154	485	19.09	172	6.77	240	9.45	240	9.45	45.00	99.0
GT12-200C	12	202	522	20.55	243	9.57	218	8.58	236	9.29	61.00	134.2
GT12-200C-2	12	205	498	19.61	259	10.20	218	8.58	238	9.37	72.00	158.4