

GT-F Range

F(Front Terminal) range is recognised worldwide as the premium battery for telecommunications/IT applications. GT-F range's reputation for 12 year long service life, combined with excellent high rate performance, makes it the number one choice for high integrity, high specification UPS systems.

GT-F front terminal monoblock's compact design and standard footprint, suitable for 19", 21", 23" and ETSI racking, give users the benefit of increased energy density, With all electrical connectors at the front, installation and inspection are simpler and quicker.

Applications

Telecom
Control Equipment
UPS

Communication Equipment
Medical Equipment
Emergency Power System



Specifications

Model	Nominal Voltage (V)	Nominal Capacity			Dimensions						Weight Approx(kg)	
		C10	C3	C1	L		W		H		(Kg)	(lb)
					(mm)	(in)	(mm)	(in)	(mm)	(in)		
GT12-50F	12	52	37.5	30	390	15.35	105	4.13	227	8.94	21.50	47.3
GT12-75F	12	78	56	45	558	21.97	105	4.13	227	8.94	31.00	68.2
GT12-85F	12	86	73	54.9	395	15.55	105	4.13	270	10.63	31.00	68.2
GT12-100F	12	100	81.6	58	558	21.97	125	4.92	227	8.94	39.00	85.8
GT12-105F	12	105	84	59	511	20.12	110	4.33	238	9.37	34.00	74.8
GT12-125F	12	125	105.9	83	558	21.97	125	4.92	270	10.63	49.00	107.8
GT12-150F	12	150	120.6	85	558	21.97	125	4.92	310	12.20	57.00	125.4
GT12-155F	12	155	124.8	88	558	21.97	124	4.88	283	11.14	54.00	118.8
GT12-170F	12	170	136.5	99	558	21.97	124	4.88	283	11.14	60.00	132.0