

GT-FG Range

With ABS thick plastic case and front terminal rock-line design, the service life of GT-F range can be 10 -12 years for normal standby and float service applications.

Applications

Telecommunication
UPS
Electric Utility



Specifications

Model	Nominal Voltage (V)	Nominal Capacity			Dimensions						Weight Approx(kg)	
		C10	C3	C1	L		W		H		(Kg)	(lb)
					(mm)	(in)	(mm)	(in)	(mm)	(in)		
GT12-50FG	12	50	35	30	390	15.35	105	4.13	227	8.94	21.50	47.3
GT12-75FG	12	75	55	45	558	21.97	105	4.13	227	8.94	31.00	68.2
GT12-85FG	12	85	73	54	395	15.55	105	4.13	270	10.63	31.00	68.2
GT12-100FG	12	100	80	56	558	21.97	125	4.92	227	8.94	39.00	85.8
GT12-105FG	12	105	82	58	511	20.12	110	4.33	238	9.37	34.00	74.8
GT12-125FG	12	125	105	83	558	21.97	125	4.92	270	10.63	49.00	107.8
GT12-150FG	12	150	120	85	558	21.97	125	4.92	310	12.20	57.00	125.4
GT12-155FG	12	155	124	88	558	21.97	124	4.88	283	11.14	54.00	118.8