


GTF - Range

In accordance with DIN (OpzS) standard, GTF range is flooded battery with tubular plate technology, and its service life is more than 20 years.

Applications

Power Plant & Hydropower Station
Photovoltaic & Solar System
Telecommunication



Model	Nominal Voltage (V)	Nominal Capacity (10hr)(Ah)	Dimensions						H Over Terminal		Weight Approx without acid (kg)	
			L		W		H		(mm)	(in)	(Kg)	(lb)
			(mm)	(in)	(mm)	(in)	(mm)	(in)				
GTF-200	2	200	103	4.06	206	8.11	354	13.94	409	16.10	13.20	29.0
GTF-250	2	250	124	4.88	206	8.11	354	13.94	409	16.10	16.20	35.6
GTF-300	2	300	145	5.71	206	8.11	354	13.94	409	16.10	19.20	42.2
GTF-350	2	350	124	4.88	206	8.11	470	18.50	525	20.67	19.40	42.7
GTF-420	2	420	145	5.71	206	8.11	470	18.50	525	20.67	23.40	51.5
GTF-500	2	500	166	6.54	206	8.11	470	18.50	525	20.67	27.40	60.3
GTF-600	2	600	145	5.71	206	8.11	645	25.39	700	27.56	33.90	74.6
GTF-800	2	800	191	7.52	210	8.27	645	25.39	700	27.56	45.30	99.7
GTF-1000	2	1000	233	9.17	210	8.27	645	25.39	700	27.56	55.50	122.1
GTF-1200	2	1200	275	10.83	210	8.27	645	25.39	700	27.56	65.80	144.8
GTF-1500	2	1500	275	10.83	210	8.27	795	31.30	850	33.46	87.00	191.4
GTF-1750	2	1750	399	15.71	214	8.43	771	30.35	826	32.52	105.00	231.0
GTF-1875	2	1875	399	15.71	214	8.43	771	30.35	826	32.52	113.00	248.6
GTF-2000	2	2000	399	15.71	214	8.43	771	30.35	826	32.52	123.00	270.6
GTF-2250	2	2250	487	19.17	212	8.35	771	30.35	826	32.52	142.00	312.4
GTF-2500	2	2500	487	19.17	212	8.35	771	30.35	826	32.52	152.00	334.4
GTF-3000	2	3000	576	22.68	212	8.35	771	30.35	826	32.52	179.00	393.8