

## **GTS** Stationary Range

GASTON GTS range utilizes thick grids of modern technology so as to guarantee the design life up to 15 years. Advanced micro porous absorbent glass mat (AGM) separator, minimizing diffusion of oxygen into the separator, reduces float charge current which suppresses the corrosion rate of the positive grid, and extends the life of the battery.

### Applications

Cable Television  
Communication Equipment  
Security System  
UPS

Control Equipment  
Medical Equipment  
Emergency Power System



### Specifications

Model	Nominal Voltage (V)	Nominal Capacity			Dimensions								Weight Approx(kg)	
		C10	C3	C1	L		W		H		Total Height		(Kg)	(lb)
					(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)		
GTS-100	2	100	75	55	101	3.98	163	6.42	200	7.87	207	8.15	7.50	16.5
GTS-200	2	200	150	110	105	4.13	183	7.20	359	14.13	371	14.61	15.50	34.1
GTS-300	2	300	225	165	146	5.75	183	7.20	359	14.13	371	14.61	22.00	48.4
GTS-400	2	400	300	220	186	7.32	183	7.20	359	14.13	371	14.61	28.50	62.7
GTS-500	2	500	375	275	227	8.94	183	7.20	359	14.13	371	14.61	35.00	77.0
GTS-600	2	600	450	330	268	10.55	183	7.20	359	14.13	612	24.09	42.50	93.5
GTS-800	2	800	600	440	169	6.65	229	9.02	600	23.62	612	24.09	60.00	132.0
GTS-1000	2	1000	750	550	204	8.03	229	9.02	600	23.62	612	24.09	73.00	160.6
GTS-1500	2	1500	1125	825	291	11.46	229	9.02	600	23.62	612	24.09	107.00	235.4
GTS-2000	2	2000	1500	1300	382	15.04	233	9.17	602	23.70	614	24.17	144.00	316.8