

GTS -G Range



In accordance with DIN 40742 (valve-regulated OpzV single cells) and utilizing Tubular & Gel electrolyte technologies, GTS-G range offers a long float life and high cycle life. The cells can be mounted horizontally or vertically, depending on requirements.

Features

Capacity from 200Ah to 3000Ah
15 years design life

No water addition required
900 cycles to 80% DOD

Applications

Telecommunication-central Office
UPS

photovoltaic& Alternative Energy System
Emergency Power System

Specifications

Model	Nominal Voltage (V)	Nominal Capacity (10hr)(Ah)	Dimensions						H Over Terminal		Weight Approx(kg)	
			L		W		H		(mm)	(in)	(Kg)	(lb)
			(mm)	(in)	(mm)	(in)	(mm)	(in)				
GTS-200G	2	200	103	4.06	206	8.11	354	13.94	380	14.96	20.00	44.0
GTS-250G	2	250	124	4.88	206	8.11	354	13.94	380	14.96	24.00	52.8
GTS-300G	2	300	145	5.71	206	8.11	354	13.94	380	14.96	29.00	63.8
GTS-350G	2	350	124	4.88	206	8.11	470	18.50	496	19.53	31.00	68.2
GTS-420G	2	420	145	5.71	206	8.11	470	18.50	496	19.53	36.00	79.2
GTS-500G	2	500	166	6.54	206	8.11	470	18.50	496	19.53	42.00	92.4
GTS-600G	2	600	145	5.71	206	8.11	645	25.39	671	26.42	50.00	110.0
GTS-630G	2	600	225	8.86	206	8.11	470	18.50	496	19.53	53.50	117.7
GTS-700G	2	700	225	8.86	206	8.11	470	18.50	496	19.53	59.50	130.9
GTS-770G	2	770	225	8.86	206	8.11	470	18.50	496	19.53	65.50	144.1
GTS-800G	2	800	210	8.27	191	7.52	645	25.39	671	26.42	68.00	149.6
GTS-1000G	2	1000	210	8.27	233	9.17	645	25.39	671	26.42	82.00	180.4
GTS-1200G	2	1200	210	8.27	275	10.83	645	25.39	671	26.42	97.00	213.4
GTS-1500G	2	1500	210	8.27	275	10.83	795	31.30	821	32.32	120.00	264.0
GTS-2000G	2	2000	212	8.35	399	15.71	772	30.39	797	31.38	160.00	352.0
GT12-2500G	2	2500	212	8.35	487	19.17	772	30.39	797	31.38	200.00	440.0
GT12-3000G	2	3000	212	8.35	576	22.68	772	30.39	797	31.38	240.00	528.0