

GTS-L Range

Special PP plastic with steel casing outside and extra thick design for battery plate, GTS-L range maximizes an outstanding performance to 20 years service life and deep cycle capacity, offering an ideal solution for large capacity valve regulated lead-

Applications

Telecommunications-Central Office
 Telecommunication-Outside Plant
 Telecommunication-Wireless
 Photovoltaic Solar System

UPS & BESS
 Electric Utility
 Emergency Power System



Specifications

Model	Nominal Voltage (V)	Nominal Capacity			Dimensions								Weight Approx(kg)	
		C10	C3	C1	L		W		H		Total Height		(Kg)	(lb)
					(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)		
GTS12-100L	12	100	75	56	437	17.20	330	12.99	218	8.58	218	8.58	66.00	145.2
GTS12-200L	12	200	150	113	665	26.18	330	12.99	218	8.58	218	8.58	106.00	233.2
GTS12-300L	12	300	225	139	893	35.16	330	12.99	218	8.58	218	8.58	153.00	336.6
GTS6-400L	6	400	300	226	623	24.53	330	12.99	218	8.58	218	8.58	104.00	228.8
GTS12-500L	12	500	375	282	957	37.68	516	20.31	218	8.58	218	8.58	234.00	514.8
GTS12-600L	12	580	450	336	1071	42.17	516	20.31	218	8.58	218	8.58	275.00	605.0
GTS6-800L	6	830	600	448	801	31.54	516	20.31	218	8.58	218	8.58	200.00	440.0
GTS6-1000L	6	1000	750	564	915	36.02	516	20.31	218	8.58	218	8.58	230.00	506.0
GTS6-1100L	6	1100	825	616	972	38.27	516	20.31	218	8.58	218	8.58	250.00	550.0
GTS6-1500L	4	1500	1125	856	793	31.22	465	18.31	277	10.91	277	10.91	255.00	561.0
GTS6-1500L	6	1500	1125	856	1147	45.16	465	18.31	277	10.91	277	10.91	370.00	814.0